

HUB USB 2.0 + Card Reader 60 in 1

1. Conforms to USB specification Rev. 1.1, 2.0

HUB USB 2.0

- 2. 480Mbps high speed data transmission
- Supports 1 device address and 2 end points adds ports: 3 ports hub
- 4. Supports suspend/normal mode power management
- 5. Supports power management for downstream port devices
- 6. Automatic switching between self/bus powered mode

Slot 1: CF 1, CF 11, Ultra 11 CF, CF Ultimate, Extreme CF, Extreme 111 CF, Extreme 1V CF, CF Elite pro, CF Pro, CF Pro 11, HS CF, XS-XS CF, Hitachi MD, IBM MD, Magic Stor.

Slot 2: XD, XD Type H, XD Type M.

Slot 3: T-flash, Micro SD

Slot 4: MS, MS-MG, MS-Pro-MG, HS-MS-Pro-MG, MS Duo 32MB, MS Duo-MG, MS Pro-Duo-MG, HS-MS Pro-Duo-MG, MS Pro Duo-psp, MS Pro Duo-Gaming. Slot 5: SD, SD-ultra, SD-Compatible, SD-Pro, SD-Ultra 11, SD-Ultra 11 plus, SD-Pleomax, SD-Pro Compatible, SD-Extreme 111 ,SD-Ultra X, SD-Turbo, SD-Super, SD-Max, Mini SD, Mini SD Pro, Mini SD-Pleomax, MMC 1GB, MMC-Pleomax, High Speed MMC, MMC-Plus(8bit), MMC-Plus Turbo, RS MMC, RS MMC-Pleomax, RS MMC-Speed, RS MMC-Max, MMC Pro, MMC Mobile, MMC Mobile-pro Compatible, MMC Mobile-Pocket, SDHC.

English	Italiano	Español	Français	FHU32165
Number of Ports	Numero di porte	Nùmero de puertos	Nombre de ports	N°. 3 x USB - 2.0 (1.1) N° 5 Slot x Card Reader
Transfer rate up to	Velocità di Trasmissione, fino a	Velocita de trasmisiòn hasta	Velocita de transmission e jusqu'à	480 Mbps
Power	Alimentazione	Alimentaciòn	Alimentation	DC Adapter 5V - 1A
Power Led	Spia di Accensione	Spy Energia	Puissance a menè	n. 1
Package Contents	Contenuto della confezione	Contenido del envase	Contenu du paquet	HUB USB 2.0 + Card Reader 60 in 1, DC Apapter 5V - 2A, Cable USB
Os Support	Sistemi Operativi Supportati	Sistemas Operativos Compatibles	Support du Système d'exploitation	Windows 98, NT,2000, 2003, XP, Vista, Mac OS

480 MBPS HIGH SPEED

RUBBER COATED SURFACE

**60 CARD READ** 

**EASY PLUG & PLAY** 



